AD-A264 672



ITATION PAGE

Form Approved OMB No. 0704-018

require reporting burden for this consistency intermation is estimated to average 1 hours per requirement of the true to the second of the consistency of the consist SEED OF THE VIOLENCE CONTRACTOR

1 AGENCY USE ONLY (Leave trans)

2 REPORT DATE

Professional Paper

4 TITLE AND SUBTITLE

March 1993

5 Fulsistanta Citiblina

A TERRAIN PARABOLIC EQUATION MODEL (TPEM)

6 AUTHOR(S)

PR: CDB6 PE: 0602435N WU: DN488760

A. E. Barrios 7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)

Naval Command, Control and Ocean Surveillance Center (NCCOSC) RDT&E Division San Diego, CA 92152-5001

8 PERFORMING CRIGANIZATION REPORT NUMBER

9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)

Naval Command, Control and Ocean Surveillance Center (NCCOSC) RDT&E Division San Diego, CA 92152-5001

10 SPONSCRING/MONITORING AGENCY REPORT NUMBER

11. SUPPLEMENTARY NOTES

12a DISTRIBUTION/AVAILABILITY STATEMENT

Approved for public release; distribution is unlimited.

DISTRIBUTIO

13. ABSTRACT (Maximum 200 words)

A numerically efficient method has been developed to model tropospheric radiowave propagation over irregular terrain in the presence of range-dependent, non-standard environmental conditions. The model is based on a modification to the smooth-earth parabolic equation, and uses the split-step Fourier algorithm developed by Hardin and Tappert.











Published in VRSI National Radio Science Meeting Proceedings, Jan 1993, p 107.

14 SUBJECT TERMS

15. NUMBER OF PAGES

propagation assessment environmental data

command and control tactical decision aids

16 PRICE CODE

17. SECURITY CLASSIFICATION OF REPORT

18. SECURITY CLASSIFICATION OF THIS PAGE

19. SECURITY CLASSIFICATION OF ABSTRACT

20. LIMITATION OF ABSTRACT


UNCLASSIFIED

UNCLASSIFIED

UNCLASSIFIED

SAME AS REPORT

	216 TELEVINORE AN ISHEAR COUNTY	210 Geo. 4 5+1453
A. E. Barrios	(619) 553-1429	Code 543



A TERRAIN PARABOLIC EQUATION MODEL (TPEM)

Amalia E Barrios


Naval Command, Control and Ocean Surveillance Center

RDT&E Division, Code 543 San Diego, CA 92152-5000

A numerically efficient method has been developed to model tropospheric radiowave propagation over irregular terrain in the presence of range-dependent, non-standard environmental conditions. The model is based on a modification to the smooth-earth parabolic equation, and uses the split-step Fourier algorithm developed by Hardin and Tappert (SIAM Rev. 15, p. 423, 1973).

For radiowave propagation over terrain, the parabolic equation (PE) is subject to a range-dependent boundary condition, specifically, that the field is zero at the surface (assuming horizontal polarization). Since the surface is constantly changing for any arbitrary terrain, this poses a formidable problem. The method developed here is based on "transforming" the PE through a change of variables and determining a new "modified" PE with a new range-independent boundary condition that is now easily solved. This transformation is equivalent to defining a new modified refractivity that includes a term based on the second derivative of the terrain. Conceptually, the modified refractivity, which normally accounts for the earth's curvature, is now used with an additional term to take into account the radius of curvature of each segment of the terrain.

Comparisons are made between TPEM and other existing terrain models, and against measured data. The figure below is a coverage diagram from TPEM for a terrain path in Alberta, Canada.



Page 107